

# ECS4100-26TX/ECS4100-26TX-ME

## L2+ Gigabit Ethernet Access Switch with 2 10G Uplinks



### Product Overview

The Edgecore ECS4100-26TX/ECS4100-26TX-ME switch is a Gigabit Ethernet access switch with two 10G uplink ports. The switch is ideal for Internet Service Providers (ISPs) and Multiple System Operators (MSOs) to provide home users with triple-play services with up to Gigabit bandwidth. It is also an ideal Gigabit access switch for SMB, enterprise, and campus networks. The ECS4100-26TX/ECS4100-26TX-ME switch is packed with features that bring high availability, comprehensive security, robust multicast control, and advance QoS to the network edge, while maintaining simple management. The switch also supports the most advance IPv6 management, IPv6 security, and IPv6 multicast control in accordance with the growth of IPv6 deployment. ISPs can expand their services from home to business users by providing a more reliable and resilient network (ITU-T G.8032 ERPS), L2 VPNs, and advanced OAM (Operations, Administration, and Maintenance) functions to ensure service-level agreements.

### Key Features and Benefits

#### Performance and Scalability

The Edgecore ECS4100-26TX/ECS4100-26TX-ME is a high-performance Gigabit Ethernet Layer 2+ managed switch with 88 Gbps switching capacity. The switch delivers wire-speed switching performance on all Gigabit ports, taking full advantage of existing high-performance Gigabit CPEs, PCs, 11n/ac Wi-Fi APs etc, significantly improving the responsiveness of applications and file transfer times.

The two built-in 10G SFP+ ports provide uplink flexibility, allowing the insertion of fiber or copper, Gigabit or 10G transceivers, to create up to 10Gbps high-speed uplinks to servers or service provider, corporate, or campus networks, reducing bottlenecks and increasing the performance of the access network.

The fanless design ensures noiseless operation and increases the reliability of the system. Dying-gasp support detects a loss of power, allowing 200 milliseconds for the system to notice the administrator through an SNMP trap or OAM.

The ECS4100-26TX-ME provides dual power inputs for AC or DC.

The ECS4100-26TX-ME provides 6KV surge protection on Ethernet ports, which can prevent damage to the network caused by power surges and lightning strikes.

#### Reliability and Energy Efficiency

The design of the ECS4100-26TX/ECS4100-26TX-ME incorporates high energy efficiency in order to reduce the impact on the environment. The Green Ethernet power-saving features and fanless design significantly reduce power consumption.

#### Continuous Availability

The IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability. The IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base, providing Layer 2 load sharing on redundant links up to 64 instances.

The ECS4100-26TX/ECS4100-26TX-ME supports IEEE 802.3ad Link Aggregation Control Protocol (LACP). It increases bandwidth by automatically aggregating several physical links together as a logical trunk and offers load balancing and fault tolerance for uplink connections.

The ECS4100-26TX/ECS4100-26TX-ME supports G.8032 Ethernet Ring Protection Switching with the ability for the network to detect and recover from incidents without impacting users, meeting the most demanding quality and availability requirements. Rapid recovery time when problems do occur is as low as 50 ms .

#### Enhanced Security

Port security limits the total number of devices from using a switch port and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. When a user is authenticated, the VLAN, QoS and security policy are automatically applied to the port where the user is connected, otherwise the port is grouped in a guest VLAN with limited access.

DHCP snooping allows a switch to protect a network from rogue DHCP servers that offer invalid IP addresses.

IP Source Guard prevents users from using IP addresses that were not assigned to them.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, or TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Private VLANs (traffic segmentation per port) isolate edge ports to ensure user privacy.

DAI (Dynamic ARP Inspection) is a security feature that validates Address Resolution Protocol (ARP) packets in a network. DAI allows a network administrator to intercept, log, and discard ARP packets with invalid MAC-to-IP address bindings.

Secure Shell (SSH) and Secure Sockets Layer (SSL/HTTPS) encrypt Telnet and web access to the switch, providing secure network management.

The ECS4100-26TX/ECS4100-26TX-ME also supports both RADIUS and TACACS+ authentication methods to secure your network.

### Key Features and Benefits

#### Comprehensive QoS

The ECS4100-26TX/ECS4100-26TX-ME offers advanced QoS for marking, classification, and scheduling to deliver best-in-class performance for data, voice, and video traffic at wire speed. Eight egress queues per port enable differentiated management of up to eight traffic types through the switch. Traffic is prioritized according to 802.1p and DSCP to provide optimal performance for real-time applications. Weighted Round Robin (WRR) and strict priority ensure differential prioritization of packet flows and avoid congestion of ingress and egress queues. Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allows maximum control of network resources.

#### Robust Multicast Control

IGMP snooping prevents the flooding of multicast traffic by dynamically configuring switch ports so that multicast traffic is forwarded to only those ports associated with an IP multicast receiver. IGMP increases the performance of networks by reducing multicast traffic flooding.

IGMP groups allow you to create customer packages for IP-TV channels, making switch configuration easy. IGMP Filtering prevents subscribers seeing unsubscribed IP-TV channels. And, IGMP Throttling allows you to set how many IP-TV channels a subscriber can receive simultaneously.

Multicast VLAN Registration (MVR) is designed for applications such as Media-on-Demand that send multicast traffic across an Ethernet network. Multicast VLANs are shared in the network, while subscribers remain in separate VLANs. This increases network security and saves bandwidth on core links. Multicast streams do not have to be routed in core L3 switches, which saves CPU power.

#### IPv6 Support

The switch supports a number of IPv6 features, including IPv6 Management, DHCPv6 Snooping with Option 37, IPv6 Source Guide, and MVR6.

#### Superior Management

An industry-standard command-line interface (CLI), accessed through the console port or Telnet, provides a familiar user interface and command set for users to manage the switch.

An embedded user-friendly web interface helps users to quickly and simply configure switches.

The ECS4100-26TX/ECS4100-26TX-ME supports SNMPv1,2c,3 and four-group RMON. The switch provides a complete private MIB for the configuration of most functions via the SNMP protocol.

Administrators can backup and restore firmware and configuration files via TFTP or FTP. The switch also provides the configuration of auto-provision for ease of use in large deployments.

AAA (Authentication, Authorization and Accounting) via RADIUS, TACACS+, enables centralized control of the switches. Access rights can be authorized per user and account for all actions performed by administrators.

#### Service Monitoring and Management

The ECS4100-26TX/ECS4100-26TX-ME support IEEE 802.1ag and ITU-T Y.1731, allowing service providers to monitor end-to-end services, identify connectivity and performance issues, and isolate problems from a remote location without dispatching an engineer onsite.

The switch also provides the capability to monitor service availability, delay, and delay variation for verifying SLA conformance (for billing purposes) and providing advance indication of performance degradation before a service outage occurs.

#### Virtual Private Networks

The ECS4100-26TX/ECS4100-26TX-ME supports Layer 2 VPNs by using Q-in-Q functions, where an 802.1Q tag from a customer VLAN (called CE-VLAN ID) is encapsulated in a second 802.1Q tag from a service-provider network (called an SP-VLAN ID). The switch supports rewriting the VLAN tag of egress traffic when the ingress traffic is tagged.



The switch also supports Layer 2 Protocol Tunneling for STP, CDP, VTP, PVST+, with Cisco-proprietary multicast address (01-00-0c-cd-cd-d0) replacement.

# ECS4100-26TX/ECS4100-26TX-ME

## Product Specifications

www.edge-core.com

### Features

Product Model		ECS4100-26TX	ECS4100-26TX-ME
Product Image			
Port	RJ-45 10/100/1000 BASE-T Ports	24	24
	100/1000 BASE-X SFP Ports	0	0
	Combo Gigabit (RJ-45/SFP) Ports	0	0
	SFP+ 10 Gigabit Uplink Ports	2	2
	GE out of band Management Port	No	No
	RJ-45 Console Port	1	1
	6KV Surge Protect	No	Yes
Performance	Switching Capacity	88 Gbps	88 Gbps
	Forwarding Rate	65.5 Mpps	65.5 Mpps
	Flash Memory	32 MB	32 MB
	DRAM	256 MB	256 MB
	MAC Address Table Size	16 K	16 K
	Jumbo Frames	12 KB	12 KB
	Auto-negotiation, Auto-MDI/MDIX	Yes	Yes
Mechanical	Rack Space	19"-1RU	19"-1RU
	Dimension (W x D x H) cm	44 x 22 x 4.4	44 x 22 x 4.4
	Weight	2.2 kg	2.3 kg
Power Supply	100-240 VAC, 50-60 Hz	Yes (Rear Panel)	Yes (Rear Panel)
	DC Power Input (36-60 V)	No	Yes (Front Panel)
	Max System Power Consumption (Watts)	20 W	20 W
	Dying Gasp	Yes	Yes
Environmental	Operating Temperature	0°C to 50°C	0°C to 50°C
	Storage Temperature	-40°C to 70°C	-40°C to 70°C
	Operating Humidity (non-condensing)	10% to 90%	10% to 90%
	Storage Humidity (non-condensing)	10% to 90%	10% to 90%
	Environmental Regulation Compliance: WEEE	Yes	Yes
	Environmental Regulation Compliance: RoHS	Yes	Yes
Certification	FCC Class A	Yes	Yes
	CE	Yes	Yes
	BSMI	Yes	Yes
	Safety Compliance: CB	Yes	Yes
	Safety Compliance: UL	Yes	Yes

# ECS4100-26TX/ECS4100-26TX-ME

## Product Specifications

www.edge-core.com

## Features

### L2 Features

- Tri-speed (10/100/1000BASE-T) copper interfaces
- Auto-negotiation for port speed and duplex mode
- Auto MDI/MDI-X
- Dual-speed(1G and 10G) SFP+ fiber interfaces
- SFP+ ports support:
  - IEEE 802.3ae changeable (10GBASE-SR/LR/ZR/ER),
  - IEEE 802.3z (1000BASE-SX/LX/LHX/ZX) transceivers, and 10G DAC/AOC
- Digital Diagnostic Monitoring (DDM) on 10G SFP+ ports
- Flow Control:
  - IEEE 802.3x for full-duplex mode
  - Back-Pressure for half-duplex mode
- Jumbo frames: 12KB
- Broadcast/Multicast/Unknown Unicast Storm Control
- Spanning Tree Protocol:
  - IEEE 802.1D Spanning Tree Protocol (STP)
  - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
  - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP), 64 instances
- BPDUGuard
- BPDUFILTER
- Root Guard
- Loopback detection
- Non-Spanning Tree Loopback detection
- ITU-T G.8032 Ethernet Ring Protection
  - Sub 50 msec convergence
  - Revertive operation mode
  - Multiple-ring network
- VLANs:
  - Supports 4K VLAN
  - Port-based VLAN
  - IEEE 802.1Q VLAN
  - GVRP
  - IEEE 802.1v Protocol-based VLAN
  - IP Subnet-based VLAN
  - MAC-based VLAN
  - Traffic Segmentation
- L2 Virtual Private Network
  - Q-in-Q
  - L2 Protocol tunneling (xSTP, CDP, VTP & PVST+, LLDP)
  - CDP/PVST+ Filtering
- Link Aggregation:
  - Static Trunk
  - IEEE 802.3ad Link Aggregation Control Protocol
  - Trunk groups: 16, up to 8 GE/2 10G ports per group
  - Load Balancing: SA+DA, SA, DA, SIP+DIP, SIP, DIP
- IGMP Snooping:
  - IGMP v1/v2/v3 snooping
  - IGMP Proxy reporting
  - IGMP Filtering
  - IGMP Throttling
  - IGMP Immediate Leave
  - IGMP Querier
- MVR (Multicast VLAN Registration)
  - Supports 5 multicast VLANs
- Port mirroring
- Remote port mirror (RSPAN)

### QoS Features

- Priority Queues: 8 hardware queues per port
- Traffic classification
  - IEEE 802.1p CoS
  - DSCP
  - MAC access control list (Source/Destination MAC, Ether type, Priority ID/ VLAN ID)
  - IP standard access control list (Source IP)
  - IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)
- Traffic Scheduling
  - Strict Priority
  - Weighted Round Robin
  - Strict + WRR
- Ingress policy map (police rate, remark CoS)
- Egress policy map (police rate, remark CoS/DSCP)
- Rate Limiting (ingress and egress, per port base)
  - GE: Resolution 64 Kbps ~ 1,000 Mbps
  - 10G: Resolution 64 Kbps ~ 10,000 Mbps

### Security Features

- Port security
- IEEE 802.1X port based and MAC based authentication
- Dynamic VLAN assignment
- MAC authentication
- Web authentication
- Voice VLAN
- Guest VLAN
- L2/L3/L4 access control list
  - MAC access control list (Source/Destination MAC, Ether type, Priority ID/VLAN ID)
  - IP standard access control list (Source IP)
  - IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)
- IPv6 ACL
- DHCP Snooping
- DHCP Option 82
- IP Source Guard
- PPPoE IA
- Dynamic ARP Inspection
- Denial of Service Protection
- Login Security
- RADIUS authentication
- RADIUS accounting
- TACACS + authentication
- TACACS + accounting
- TACACS + authorization
- Management Interface Access Filtering (SNMP, WEB, Telnet)
- SSH (v1.5/v2.0) for security Telnet
- SSL for HTTPS

### Green Ethernet

- IEEE 802.3az Energy-Efficient Ethernet (EEE)

# ECS4100-26TX/ECS4100-26TX-ME

## Product Specifications

www.edge-core.com

## Features

### IPv6 Features

- IPv4/IPv6 dual protocol stack
- IPv6 address types stack: Unicast
- IPv6 neighbor discovery
  - Duplicate address
  - Address resolution
  - Unreachable neighbor detection
- Stateless auto-configuration
- Manual configuration
- Remote IPv6 ping
- IPv6 Telnet support
- HTTP over IPv6
- SNMP over IPv6
- IPv6 Syslog support
- IPv6 TFTP support
- MLD Snooping v1/v2
- IPv6 source guard
- DHCPv6 snooping
- MVR6

### Management

- Switch Management:
  - CLI via console port or Telnet
  - Web management
  - SNMP v1, v2c, v3
- Firmware and Configuration:
  - Firmware upgrade via TFTP/HTTP/FTP/SFTP server
  - Multiple configuration files
  - Configuration file upload/download via TFTP/HTTP/FTP/SFTP server
- RMON (groups 1, 2, 3 and 9)
- DHCP client for IP address assignment
- DHCP dynamic provision option 66,67
- SNTP
- Syslog (Local flash)
- Remotelog (RFC3164)
- SMTP (email Notification)
- Supports LLDP (802.1ab)
- sFlow v4, v5
- Cable diagnostic
- (Optional) ECView Pro, a powerful network management software that maximizes the managed capabilities of Edgecore devices with:
  - Topology management
  - Performance management
  - Configuration management
  - Event management
  - SNMP management

### Routing

- IPv4 Static Route

### OAM

- IEEE 802.3ah Link
  - Dying gasp
- IEEE 802.1ag Connectivity Fault Management
  - Connectivity check
  - Loopback
  - Linktrace
- ITU-T Y.1731 Performance and Throughput Management
- Frame Delay
- Frame Delay variation

### Safety

- UL (CSA 22.2. NO 60950-1 & UL60950-1)
- CB (IEC60950-1)

### Electromagnetic Compatibility

- CE Mark
- FCC Class A
- CISPR Class A
- BSMI

### Environmental Specification

- Temperature:
  - 0°C to 50°C (32°F to 122°F) Standard Operating
  - 40°C to 70°C (-40°F to 158°F) Non-Operating
- Humidity: 10% to 90% (Non-condensing)

### Power Supply

- Power input
  - 100 to 240 VAC, 50/60 Hz
  - DC: 36 VDC~60 VDC (ECS4100-26TX-ME only)

### Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore Data Center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2017 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

### Ordering Information

Optional Accessories	Product Description
ET4201-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm)
ET4201-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET4201-LHX	1Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)
ET4201-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)
ET4201-RJ45	1000BASE-T RJ45 transceiver, 100 m
ET4202-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm, DDM)
ET4202-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm, DDM)
ET4202-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm, DDM)
ET4203-BX20	1Gbps, SFP (Distance: 20 km; Wavelength: Tx1310 nm / Rx1490 nm)
ET4203-BX20D	1Gbps, SFP (Distance: 20 km; Wavelength: Tx1490 nm / Rx1310 nm)
ET4204-BX10	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1310 nm / Rx1550 nm)
ET4204-BX10D	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1550 nm / Rx1310 nm)
ET4204-BX10DDMi	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1310 nm / Rx1550 nm, DDM)
ET4204-BX10DDDMi	1Gbps, SFP (Distance: 10 km; Wavelength: Tx1550 nm / Rx1310 nm, DDM)
ET5402-SR	10Gbps, Small Form Factor Pluggable (Distance: 300 m; Wavelength: 850 nm)
ET5402-LR	10Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET5402-ER	10Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1550 nm)
ET5402-ZR	10Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)
ECView Pro	Network Management Software